



Hänel Rotomat® industrial carousels at a glance

Hänel supplies a full range of Rotomat® industrial carousels, including the following. Special features and customized compartment divisions can also be ordered.

Rotomat® model	900/100	900/115	900/125	936	946	950	956	970	980	985S	986	990
Maximum payload per shelf in kg	150	150	150	250	330	400	340/400	250	600	750	500	250
Maximum payload per shelf in lbs	331	331	331	551	728	882	750/882	551	1,323	1,653	1,102	551
Maximum payload per carousel in kg	3,000	3,000	3,000	6,000	6,000	10,000	10,000	6,000	14,000	14,000	14,000	10,000
Maximum payload per carousel in lbs	6,614	6,614	6,614	13,228	13,228	22,046	22,046	13,228	30,865	30,865	30,865	22,046
Shelf depth in mm	370	428	470	630	630	428	640	445	505	505	630	640
Shelf depth in Inches	14.57	16.38	18.50	24.80	24.80	16.38	25.20	17.52	19.88	19.88	24.80	25.20
Shelf width in mm	2,243 2,838	2,243 2,838	2,243 2,847	2,915	2,915	2,870	2,870	2,915	2,750	2,750	2,750	2,870
Shelf width in Inches	88.31 111.73	88.31 111.73	88.31 112.09	114.76	114.76	112.99	112.99	114.76	108.27	108.27	108.27	112.99
Standard carousel width in mm (customized carousel widths possible)	2,600 2,847	2,600 3,270	2,600 3,280	3,420	3,420	3,420	3,420	3,420	3,420	3,420	3,420	3,420
Standard carousel width in Inches (customized carousel widths possible)	102.36 128.74	102.36 128.74	102.36 129.13	134.65	134.65	134.65	134.65	134.65	134.65	134.65	134.65	134.65
Carousel depth in mm	1,000	1,155	1,255	1,615	1,615	12,250	1,670	12,250	1,475	1,600	1,720	1,670
Carousel depth in Inches	39.37	45.47	49.41	63.58	63.58	49.21	65.75	49.21	58.07	62.99	67.72	65.75

package												
Frequency converter for gentler, smoother start	✘	✘	✘	✘	✘	✘	✘	✘	✘	✘	✘	✘

✓ = Standard

✘ = Optional