

Maximum customization options

The right system model for every application

Technical data

Model	Device dimensions in Inch		Container sizes in Inch		Load capacity in lbs
	Depth	Width	Width	Depth	
840-635	88.19	45.87	33.07	25.00	661/1,102/1,543
1300-635	88.19	63.98	51.18	25.00	661/1,102/1,543/2,205
1640-635	88.19	77.36	64.57	25.00	661/1,102/1,543/1,984
1860-635	88.19	86.02	73.23	25.00	551/1,102/1,433/1,984
2060-635	88.19	93.90	81.10	25.00	551/1,102/1,433/1,874
2300-635	88.19	103.35	90.55	25.00	551/882/1,036/1,323/1,764
2460-635	88.19	109.65	96.85	25.00	551/882/1,036/1,323/1,764
2860-635	88.19	125.39	112.60	25.00	419/551/882/1,102/1,213/1,433
3060-635	88.19	133.27	120.47	25.00	419/551/772/992/1,213/1,378
3260-635	88.19	141.14	128.35	25.00	397/551/882/1,213/1,323
3660-635	92.55	166.14	144.09	25.00	1,102/1,543
4060-635	92.55	181.88	159.84	25.00	1,102/1,543
4460-635	92.55	197.63	175.59	25.00	882/1,323
840-825	110.63	45.87	33.07	32.48	661/1,102/1,543/2,205
1300-825	110.63	63.98	51.18	32.48	661/1,102/1,543/2,205
1640-825	110.63	77.36	64.57	32.48	661/1,102/1,543/1,984
1860-825	110.63	86.02	73.23	32.48	551/1,102/1,433/1,984
2060-825	110.63	93.90	81.10	32.48	551/1,102/1,433/1,874
2300-825	110.63	103.35	90.55	32.48	551/1,036/1,323/1,764
2460-825	110.63	109.65	96.85	32.48	551/1,036/1,323/1,764
2860-825	110.63	125.39	112.60	32.48	419/551/882/1,102/1,213/1,433
3060-825	110.63	133.27	120.47	32.48	397/717/937/992/1,213/1,378
3260-825	110.63	141.14	128.35	32.48	397/551/882/1,213/1,323
3660-825	114.57	166,14	144.09	32.48	1,102/1,543
4060-825	114.57	181,89	159.84	32.48	1,102/1,543
4460-825	114.57	197,63	175.59	32.48	882/1,323
840-1047	136.81	45.87	33.07	41.22	661/1,102/1,543/2,205
1300-1047	136.81	63.98	51.18	41.22	661/1,102/1,543/2,094
1640-1047	136.81	77.36	64.57	41.22	551/1,102/1,433/1,874
1860-1047	136.81	86.02	73.23	41.22	551/992/1,433/1,874
2060-1047	136.81	93.90	81.10	41.22	551/992/1,323/1,653
2460-1047	136.81	109.65	96.85	41.22	551/882/1,323/1,653
2860-1047	136.81	125.39	112.60	41.22	551/772/1,102/1,543
3060-1047	136.81	133.27	120.47	41.22	485/661/992/1,433
3260-1047	136.81	141.14	128.35	41.22	485/661/992/1,323
840-1270	163.39	45.87	33.07	50.00	661/1,102/1,543/2,205
1300-1270	163.39	63.98	51.18	50.00	661/1,102/1,543/1,984
1640-1270	163.39	77.36	64.57	50.00	551/1,102/1,433/1,764
1860-1270	163.39	86.02	73.23	50.00	551/992/1,433/1,764
2060-1270	163.39	93.90	81.10	50.00	551/882/1,323/1,653
2460-1270	163.39	109.65	96.85	50.00	551/882/1,323/1,543
2860-1270	163.39	125.39	112.60	50.00	441/661/1,102/1,543
3060-1270	163.39	133.27	120.47	50.00	441/551/992/1,433
3260-1270	163.39	141.14	128.35	50.00	441/551/992/1,323

Maximum device payload up to 60,000 kg / 132,450 lbs depending on the model. A few examples from a multitude of possibilities.

Contact the storage specialists at Hänel

They will calculate the optimal system and container dimensions for your storage needs.